

69-05-00
A
LIMBACH & LIMBACH L.L.P.
2001 Ferry Building, San Francisco, CA 94111
415/433-4150

Address to:

Box Patent Application
Assistant Commissioner for Patents
Washington, D.C. 20231

Attorney's Docket No. SONY-U0095

First Named Inventor YOSHINORI MATSUMOTO

UTILITY PATENT APPLICATION TRANSMITTAL
(under 37 CFR 1.53(b))

SIR:

Transmitted herewith for filing is the patent application entitled:
OPTICAL DISK APPARATUS, FOCUS-VALUE CORRECTING METHOD, AND OPTICAL DISK

CERTIFICATION UNDER 37 CFR § 1.10

I hereby certify that this New Application and the documents referred to as enclosed herein are being deposited with the United States Postal Service on this date August 31, 2000, in an envelope bearing "Express Mail Post Office To Addressee" Mailing Label Number EL254113275US addressed to: Box Patent Application, Assistant Commissioner for Patents, Washington, D.C. 20231.

Joan Mazzeo

(Name of person mailing paper)

gm
(Signature)

Enclosed are:

1. ☒ Transmittal Form (two copies required)
2. The papers required for filing date under CFR § 1.53(b):
 - i. 20 Pages of specification (including claims and abstract);
 - ii. 7 Sheets of drawings.
☒ formal ☐ informal
3. Declaration or oath
 - a. ☒ Newly executed (original or copy) Combined with Power of Attorney

ACCOMPANYING APPLICATION PARTS

4. ☒ An assignment of the invention to Sony Corporation is attached (including Form PTO-1595).
 - i. ☐ 37 CFR 3.73(b) Statement (when there is an assignee)
5. ☒ Power of Attorney (Combined with Declaration)
6. ☐ An Information Disclosure Statement (IDS) is enclosed, including a PTO-1449 and copies of ☐ references.
7. ☐ Preliminary Amendment.
8. ☒ Return Receipt Postcard (MPEP 503 -- should be specifically itemized)
9. FOREIGN PRIORITY
 - [x] Priority of application no. P11-262684 filed on September 16, 1999 in Japan is claimed under 35 USC 119.

The certified copy of the priority application:

- ☒ is filed herewith; or
☐ has been filed in prior application no. ☐ filed on ☐, or
☐ will be provided.

☐ English Translation Document (if applicable)

10. FEE CALCULATION

- a. ☐ Amendment changing number of claims or deleting multiple dependencies is enclosed.

CLAIMS AS FILED

	Number Filed	Number Extra	Rate	Basic Fee (\$690)
Total Claims	11 - 20	* 0	x \$18.00	0
Independent Claims	3 - 3	* 0	x \$78.00	0
<input type="checkbox"/> Multiple dependent claim(s), if any			\$260.00	0

*If less than zero, enter "0".

Filing Fee Calculation \$690.00

50% Filing Fee Reduction (if applicable) \$

11. Small Entity Status

- a. ☐ A small entity statement is enclosed.
b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
c. ☐ is no longer claimed.

12. Other Fees

- ☒ Recording Assignment [\$40.00] \$40.00
☐ Other fees
Specify _____ \$0

Total Fees Enclosed \$730.00

13. Payment of Fees

- ☒ Check(s) in the amount of \$ 730.00 enclosed.
☐ Charge Account No. 12-1420 in the amount of \$____.
A duplicate of this transmittal is attached.

14. All correspondence regarding this application should be forwarded to the following attorney:

Charles P. Sammut
Limbach & Limbach L.L.P.
2001 Ferry Building
San Francisco, CA 94111
Telephone: 415/433-4150
Facsimile: 415/433-8716

15. Authorization to Charge Additional Fees


- ☒ The Commissioner is hereby authorized to charge any additional fees (or credit any overpayment) associated with this communication and which may be required under 37 CFR § 1.16 or § 1.17 to Account No. 12-1420. **A duplicate of this transmittal is attached.**

LIMBACH & LIMBACH L.L.P.

August 31, 2000
(Date)

Attorney Docket No. SONY-U0095
[S00P1095US00]

By:


Mayumi Maeda
Registration No. 40,075
Attorney(s) or Agent(s) for Applicant(s)

TITLE OF THE INVENTION

Optical Disk Apparatus, Focus-Value Correcting Method, and Optical Disk

BACKGROUND OF THE INVENTION

The present invention relates to an optical disk apparatus for recording and reproducing data on and from an optical disk. More particularly, the invention relates to an optical disk apparatus which can correct a focus value accurately within a short time and which can thus have good recording/reproducing characteristic. The invention also relates to a focus-value correcting method that can correct a focus value accurately within a short time. The invention further relates to an optical disk.

In the field of optical disk apparatuses for recording and reproducing data on and from optical disks, compact disks (CDs) having audio signals recorded on them have already been in use in large numbers. Recently, digital versatile disks (DVDs), which have a large storage capacity and from which data can be transferred at high rate, have come into use as media for recording motion pictures. In addition, MO (Magneto-Optical) disks, PDs (Phase-Change Disks) and DVD-RAMs have been put to practical use as recording/reproducing disks.

Thanks to the advanced microprocessor technology and the like, not only text data, but also audio data, still-picture data, motion-picture data and the like can be recorded on and reproduced from the above-mentioned various kinds of disks. It is therefore increasingly demanded that disk systems be developed which have a storage

capacity large enough to store these various items of data and which can change the rate of transferring the data.

To increase the data storage capacity of the optical disk system, it is generally necessary to reduce the size of the beam spot in the operation of recording and reproducing data on and from the disk, thereby to record data at high density on the optical disk. The size a of a beam spot is given as follows:

$$a = \alpha \times \lambda / \text{NA}$$

where α is the constant determined by the distribution of light beam intensity, λ is the wavelength of the light beam, and NA is the numerical aperture of the objective lens provided in the optical disk system.

Thus, a small beam spot can be formed on the surface of the optical disk if the optical disk system has a semiconductor laser for emitting a beam of short wavelength and an objective lens having a large NA value. If so, the system can record data at high density on the optical disk and can thereby have a large storage capacity.

If the beam spot is made small by this method, however, the focal depth will decrease. In other words, the tolerance for defocusing (i.e., focusing error) will inevitably decrease. The focal depth d is usually expressed as follows:

$$d \propto \lambda / (\text{NA})^2.$$

That is, the shorter the wavelength of the light beam and the larger the NA, the more the focal depth will decrease. In the optical disk apparatus for recording and reproducing data on and from an optical disk at high density, high-precision focusing

control should, therefore, be performed to place the recording surface of the disk within the focal depth of the objective lens.

The defocusing occurs in the focusing control, due to various causes. It may result from the steady-state deviation that has not been eliminated completely during the servo control. It may result from the difference between optical disks in terms of substrate thickness. It may be caused by the changes in the servo target value, due to the offset changes that occur as the temperature rises in the optical disk apparatus.

Of these causes of defocusing, the steady-state deviation is determined by the size and gain of the focus-disturbing element. In most cases of high-density, data-recording/reproducing, the disturbance (e.g., warping of the disk) are reduced and the gain of the focus-disturbing element are increased, thereby minimizing the steady-state deviation. To reduce the defocusing resulting from the difference between optical disks in substrate thickness, thereby to raise the focusing precision, the focus may be automatically adjusted in accordance with the jitter value or the like of the ROM section. In this case, it suffices to change the focus bias to various values and select the most desirable one in accordance with the jitter value detected at the time of inserting the disk is inserted into the optical disk apparatus.

While the optical disk apparatus is operating, it is difficult to eliminate the offset change or the like resulting from the temperature rise in the optical disk apparatus. To eliminate the offset change or the like during the operation of the optical disk apparatus, the change of the offset must be detected at short intervals by

simple means, thereby to move the focus to an optimal point. In practice, however, the change of the offset can hardly be detected at short intervals by simple means during the operation of the optical disk apparatus.

BRIEF SUMMARY OF THE INVENTION

The present invention has been made in view of the foregoing. The first object of the invention is to provide an optical disk apparatus which can correct a focus value accurately within a short time and which can thus have good recording/reproducing characteristic. The second object of this invention is to provide a focus-value correcting method that can be used in an optical disk apparatus to correct a focus value. The third object of the invention is to provide an optical disk with which the method can be employed to correct a focus value.

To attain the first object, an optical disk apparatus according to the present invention is designed to record and reproduce data on and from an optical disk having a signal-recording surface. The apparatus comprises: optical head means for applying a light spot to the signal-recording surface of the optical disk; focusing control means for controlling the focusing operation the optical head means performs to place the signal-recording surface of the optical disk within a focal distance of the light spot applied by the optical head means; evaluation-function generating means for generating an evaluation function for correcting a focus value set in the focusing control means, in accordance with signals the optical head means has generated from

light reflected from the optical disk; and control means for setting an initial focus value at a point where the evaluation function generated by the evaluation-function generating means is minimal or maximal, for setting an observation point deviating from the point where the initial focus value is set, and for correcting the initial focus value in accordance with changes in the evaluation function at the observation point.

To achieve the second object, a focus-value correcting method according to the invention is designed for use in focusing control for placing the signal-recording surface of an optical disk within the focal depth of a light spot an optical head has applied to the optical disk. The method comprises the steps of: setting an initial focus value at a point where an evaluation function for correcting a focus value set in the focusing control means is minimal or maximal, said evaluation function having been generated from signals the optical head means has generated from light reflected from the optical disk; setting an observation point deviating from the point where the initial focus value is set, and acquiring the first evaluation function at the observation point thus set; determining the timing at which to correct the focus value to perform the focusing control; acquiring the second evaluation function at the observation point at the timing determined; and correcting the initial focus value in accordance with a difference between the first evaluation function and the second evaluation function.

To accomplish the third object, an optical disk according to this invention has a signal-recording surface that is placed within a focal depth of a light spot applied on the signal-recording surface by an optical head, during focusing control. The disk

further has: a servo region on the signal-recording surface; and an evaluation-function recording area provided at a prescribed part of the servo region, for recording evaluation functions that are applied to correct a focus value for use in the focusing control.

As described above, the observation point, at which to correct the focal value to achieve reliable focusing control, is deviated from an optimal point, whereby the focal value is corrected accurately within a short time. The optical disk apparatus of the invention can therefore have good recording/reproducing characteristic.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

FIG. 1 is a block diagram of an optical disk apparatus according to this invention;

FIG. 2 is a block diagram showing the major components of the optical disk apparatus;

FIG. 3 is a diagram illustrating an optical disk on and from which the optical disk apparatus records and reproduce data;

FIG. 4 is a flowchart explaining the operation of the optical disk apparatus;

FIG. 5 is an evaluation-function characteristic diagram for explaining the relation between a focus value set and an observation point;

FIG. 6 is an evaluation-function characteristic diagram explaining how the optimal focus point and the observation point move when the temperature rises; and

FIG. 7 is an evaluation-function characteristic diagram explaining how the optimal focus point and the observation point move when the temperature falls.

DETAILED DESCRIPTION OF THE INVENTION

An embodiment of the present invention will be described, with reference to the accompanying drawings. The embodiment is an optical disk apparatus that has an optical head 2 as shown in FIG. 1. The apparatus is designed to record and reproduce data on and from the signal-recording surface of an optical disk 1.

The optical disk apparatus comprises, in addition to the optical head 2, a matrix circuit 3, a PLL circuit 4, an evaluation-function generating circuit 5, a controller 6, and a servo circuit 7. The matrix circuit 3 generates various error signals and the like from the output of the optical head 2. The PLL circuit 4 generates a system clock signal from the RF reproduced signal generated by the matrix circuit 3. The system clock signal is supplied to the evaluation-function generating circuit 5. The evaluation-function generating circuit 5 generates an evaluation function (later described) from the jitter the PLL circuit 4 has generated. The controller 6 controls the servo circuit 7 in accordance with the evaluation function generated by the evaluation-function generating circuit 5. The servo circuit 7 performs focusing control as will be described later in detail, under the control of the controller 6.

The optical disk apparatus further comprises an interface circuit 8, an ECC circuit 9, a modulator 10, and a record-waveform control circuit 11. The interface

circuit 8 connects the ECC circuit 9 to an external host computer (not shown). The ECC circuit 9 receives a commands and data from the external host computer via the interface circuit 8 and adds data-correcting codes to the data. The modulator 10 modulates the output of the ECC circuit 9. The record-waveform control circuit 11 converts the data output from the modulator 10 to a record signal of an appropriate magnitude. The record signal is supplied to the optical head 2, which records marks on the optical disk 1 in accordance with the waveform of the record signal.

The optical disk apparatus further comprises a waveform-equalizing circuit 12, a data-extracting circuit 13, and a demodulator 14. The waveform-equalizing circuit 12 equalizes the waveform of the RF signal supplied from the matrix circuit 3. The data-extracting circuit 13 extracts binary data from the output of the waveform-equalizing circuit 12. The demodulator 14 demodulates the binary data output from the data-extracting circuit 13.

To record data on the optical disk 1, the ECC circuit 9 receives commands and data from the external host computer through the interface circuit 8 and adds data-correcting codes to the data. The output of the ECC circuit 9 is supplied to the modulator 10. The modulator 10 modulates the data output from the ECC circuit 9. The data modulated is supplied to the control circuit 11, which converts the data to a record signal of an appropriate magnitude. The record signal is supplied to the optical head 2. The head 2 generates a laser beam having intensity that corresponds to the waveform of the record signal. The optical head 2 applies a laser beam is applied to

the optical disk 1, whereby the data is recorded on the optical disk 1.

To reproduce the data from the optical disk 1, the waveform-equalizing circuit 12 equalizes the waveform of the RF signal supplied from the matrix circuit 3. The data-extracting circuit 13 extracts binary data from the output of the waveform-equalizing circuit 12. The demodulator 14 demodulates the binary data output from the data-extracting circuit 13. The ECC circuit 9 corrects reading errors, if any, resulting from the defects made in the recording surface of the disk 1. The binary data, thus corrected, is supplied to the external host computer through the interface circuit 8.

The servo circuit 7 receives various error signals from the matrix circuit 3. In accordance with the error signals, the servo circuit 7 performs focusing control, tracking control, thread control and the like, thereby accurately positioning the beam spot on the optical disk 1, said beam spot pertaining to the laser beam the optical head 2 is applying to the optical disk 1. The present invention is applied to the focusing control, in which the signal-recording surface of the optical disk 1 is placed within the focal depth of the objective lens incorporated in the head 2. The focusing control achieved by the servo circuit 7 is affected by the changes in the offset, which have resulted from a temperature rise and the like in the optical disk apparatus.

The initial focus value set in the servo circuit 7 is therefore corrected in the optical disk apparatus, as will be described below.

First, the evaluation-function generating circuit 5 generates an evaluation

function from the signal the matrix circuit 3 has generated from the light beam reflected from the optical disk 1 and detected by the optical head 2. More precisely, the circuit 5 generates the evaluation function from the jitter which the PLL circuit 4 generates when it generates the system clock signal from the RF signal supplied from the matrix circuit 3. The evaluation function, thus generated, will be used in the focusing control. The evaluation-function generating circuit 5 may generate the evaluation function from the amplitude of the RF signal, not from the jitter the PLL circuit 4 generates. The evaluation function thus generated is read by the controller 6.

The controller 6 corrects the focus value by performing the focus-value correcting method according to this invention. In the method (later described in detail), an initial focus value is set at a point where the evaluation function is minimal, and an observation point is set, which is deviated from the point where the initial focus value is set. The controller 6 corrects the initial focus value, thus set in the servo circuit 7, in accordance the change in the evaluation function at the observation point.

The servo circuit 7 uses the focus value corrected by the controller 6, thereby accomplishing focusing control. FIG. 2 shows the servo circuit 7 and the components peripheral to the circuit 7. As shown in FIG. 2, the focus value, thus corrected, is supplied from the controller 6 to the comparator circuit 15 provided in the servo circuit 7. A focus error signal is supplied from the matrix circuit 3 to the comparator circuit 15. The comparator circuit 15 compares the focus error signal with the focus value,

finding the difference between the focus error and the focus value. The comparator circuit 15 supplies a drive signal to a coil 2a through a drive amplifier 16, until the difference between the focus error and the focus value decreases to nil. Focusing control is thereby performed on the optical head 2.

The optical disk 1 will be described with reference to FIG. 3. As FIG. 3 shows, the optical disk 1 has a recording region 21, a ROM region 22, and four pit regions 23 on its recording surface. Each pit region 23 consists of a sector mark (SM) region 24, a VFO area 25, a preamble (PA) area 26, an address mark (AM) area 27, an address ID data (ID) area 28, and a focus adjustment (FA) area 29. A sector mark is recorded in the SM area 24 to achieve ordinary pit addressing. The VFO area 25 is provided to accomplish PLL data extraction. The address data designating the positions of tracks and the random data for use in focus adjustment are recorded on the optical disk 1. Nonetheless, the random data may not be recorded and the address data may be used to achieve focus adjustment, as well. The ROM region 22 and the pit regions 23 are optically equivalent in terms of linear density, track pitch and the like. As the optical disk 1 is rotated in the direction of arrow 30, the beam spot that the laser beam emitted from the head 2 forms on the optical disk 1 moves on each pit region 23 in the direction of arrow 31.

Track numbers are sparsely described in the SM area 24 in the form of patterns that can be easily read. The VFO region 25 is provided to achieve PLL operation to prevent a synchronization in the ID area 28. The PA area 26 is a so-called "guard

area". The AM area 27 has been subjected to PLL operation, indicating that the ID area 28 will follow next. The ID area 28 is necessary to record the track number, sector number and other data in one track.

The FA area 29 is provided to set a focus value for performing focusing control in the optical disk apparatus. In the FA area 29 there is described, for example, a random carrier pattern. The evaluation-function generating circuit 5 uses the random carrier pattern to measure the jitter the PLL circuit 4 has generated. At the end of the ID area 28, the focus-changing operation starts, measuring the jitter by using the random carrier pattern.

As shown in FIG. 3, the four pit regions 23 are arranged, forming a cross. Hence, the optical disk apparatus carries out focusing control four times, every time the optical disk 1 is rotated once.

How the optical disk apparatus performs the focusing control with respect to the optical disk 1 will be explained, with reference to the flowchart of FIG. 4. The flow chart shows the sequence of correcting the focus value set, or the focus-value correcting method according to the present invention. It is the controller 6 that effects the focus-value correcting method.

In Step S1, the optical disk 1 is inserted into the optical disk apparatus. In Step S2, the optical head 2 is moved to the ROM region 22, i.e., the innermost circular track of the disk 1. Hill-climbing method, for example, is performed, thus correcting the focus value so that the evaluation function may become minimal.

As described above, the evaluation function is generated from the jitter the PLL circuit 4 has generated. Instead, the function may be one which changes like a quadratic function, with the degree of defocusing represented by the amplitude of the smallest mark and which is sufficiently sensitive to the defocusing. In Step S3, an initial focus value f_b is set. At the same time, an observation point f_0 is set as is illustrated in FIG. 5. Preferably, the observation point f_0 is one before and after which the servo system operates reliably and which deviates as much as possible from the initial focus value f_b . A focus value is set at the observation point f_0 , thereby acquiring an evaluation function $F(f_0)$ at the observation point f_0 . The evaluation function $F(f_0)$ is stored into a memory or the like.

Thereafter, the initial focus value f_b is applied. In Step S4, the optical disk apparatus records data on the optical disk 1 or reproduces data from the optical disk 1. In Step S5 it is determined whether the data has been recorded or reproduced completely. If it is determined that the data has not been completely recorded or reproduced, the focus value is temporarily shifted to the observation point f_0 in the focus adjustment (FA) area 29 of each pit region 23 that periodically appears because it is provided on the rotating optical disk 1. Then, an evaluation function $F'(f_0)$ is acquired at this time. This evaluation function $F'(f_0)$ may be greater than the evaluation function $F(f_0)$ previously acquired, that is:

$$F'(f_0) > F(f_0)$$

In this case, the evaluation function $F'(f_0)$ indicates that the focus value

contains an offset or the like that has resulting from, for example, the temperature rise and the like in the optical disk apparatus. In other words, the evaluation function has undergone an apparent change. Thus, the initial focus value f_b is changed to a focus value $f'b$, whereby the focus value is set at the optimal point again. At this time, the observation point f_0 is set anew to $f'0$, which is defined as follows:

$$f'0 = f_0 + (f'b - f_b)$$

The evaluation function $F'(f_0)$ may be smaller than the evaluation function $F(f_0)$ previously acquired, that is:

$$F'(f_0) < F(f_0)$$

If this is the case, the evaluation function $F'(f_0)$ indicates that the temperature in the optical disk apparatus has fallen. Thus, the initial focus value f_b is changed to a focus value $f'b$ as shown in FIG. 7, in accordance with the absolute value of the difference between the function $F'(f_0)$ and the function $F(f_0)$.

As has been described, the focus-value correcting method according to the invention can correct the change in a servo target value, due to the offset contained in the focus value, in both magnitude and direction, by measuring the evaluation function at one observation point only. Since the evaluation function is minimal at the observation point, the focus value can be corrected, even while the head 2 is recording data on the disk 1 or reproducing data from the disk 1, since the optical disk 1 has pit regions 23. Thus, the defocusing can be reliably minimized during the data-recording operation and data-reproducing operation. This enables the optical disk apparatus to

record and reproduce data on and from the optical disk 1 at high density.

The focus value for focusing control may be corrected every time the optical disk 1 is rotated a prescribed number of times. Alternatively, the focus value may be corrected whenever the temperature in the optical disk apparatus changes by a predetermined value. Still alternatively, the focus value may be corrected at regular time intervals. The CPU 6 determines the timing of correcting the focus value from the number of times the optical disk 1 has been rotated, from the changes of temperature in the optical disk apparatus, or from the time that has elapsed.

WHAT IS CLAIMED IS:

1. An optical disk apparatus for recording and reproducing data on and from an optical disk having a signal-recording surface, said apparatus comprising:

optical head means for applying a light spot to the signal-recording surface of the optical disk;

focusing control means for controlling the focusing operation the optical head means performs to place the signal-recording surface of the optical disk within a focal distance of the light spot applied by the optical head means;

evaluation-function generating means for generating an evaluation function for correcting a focus value set in the focusing control means, in accordance with signals the optical head means has generated from light reflected from the optical disk; and

control means for setting an initial focus value at a point where the evaluation function generated by the evaluation-function generating means is minimal or maximal, for setting an observation point deviating from the point where the initial focus value is set, and for correcting the initial focus value in accordance with changes in the evaluation function at the observation point.

2. The optical disk apparatus according to claim 1, wherein the evaluation-function generating means generates an evaluation function that changes like a quadratic function with a degree of defocusing, and the control means sets the initial focus value at the point where the evaluation function is minimal.

3. The optical disk apparatus according to claim 2, wherein the control

means increases the initial focus value in direct proportion to the evaluation function at the observation point.

4. The optical disk apparatus according to claim 2, wherein the control means decreases the initial focus value in direct proportion to the evaluation function at the observation point.

5. The optical disk apparatus according to claim 1, wherein the control means corrects the focus value set in the focusing control means, every time the optical disk rotates a prescribed number of times.

6. The optical disk apparatus according to claim 1, wherein the control means corrects the focus value set in the focusing control means, every time the temperature in the apparatus changes by a prescribed value.

7. The optical disk apparatus according to claim 1, wherein the control means corrects the focus value set in the focusing control means, at regular time intervals.

8. The optical disk apparatus according to claim 1, wherein the control means corrects the focus value set in the focusing control means, in accordance with the light reflected from the optical disk.

9. A focus-value correcting method for use in focusing control for placing the signal-recording surface of an optical disk within the focal depth of a light spot on an optical head has applied to the optical disk, said method comprising the steps of:

setting an initial focus value at a point where an evaluation function for

correcting a focus value set in the focusing control means is minimal or maximal, said evaluation function having been generated from signals the optical head means has generated from light reflected from the optical disk;

setting an observation point deviating from the point where the initial focus value is set, and acquiring the first evaluation function at the observation point thus set;

determining the timing at which to correct the focus value to perform the focusing control;

acquiring the second evaluation function at the observation point at the timing determined; and

correcting the initial focus value in accordance with a difference between the first evaluation function and the second evaluation function.

10. An optical disk having a signal-recording surface that is placed within a focal depth of a light spot applied on the signal-recording surface by an optical head, during focusing control, said disk having:

a servo region on the signal-recording surface; and

an evaluation-function recording area provided at a prescribed part of the servo region, for recording evaluation functions that are applied to correct a focus value for use in the focusing control.

11. The optical disk according to claim 10, wherein data from which the evaluation functions are generated is recorded, in the form of pits, in the evaluation-

function recording area.




FIG.2




FIG.3




FIG.4

001680" 101025800




FIG.5




FIG.6




FIG.7

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。	As a below named inventor, I hereby declare that:
私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。	My residence, post office address and citizenship are as stated next to my name.
下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。	I believe I am the original, first and sole inventor (if only one named is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled. OPTICAL DISK APPARATUS, FOCUS-VALUE CORRECTING METHOD, AND OPTICAL DISK
上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、 <input type="checkbox"/> 月 日に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、 （該当する場合） _____ に訂正されました。	the specification of which is attached hereto unless the following box is checked: <input type="checkbox"/> was filed on _____ as United States Application Number or PCT International Application Number _____ and was amended on _____ (if applicable).
私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。	I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.
私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。	I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.
私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国以外の国の少なくとも一ヶ国を指定している特許協力条約365(a)項に基づき国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。	I hereby claim foreign priority under Title 35, United States Code, Section 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

S00P1095US00

Japanese Language Declaration
日本語宣言書

<p>Prior Foreign Application(s) 外国での先行出願</p> <p>P11-262684 (Number) (番号)</p> <p>Japan (Country) (国名)</p> <p>16/09/1999 (Day/Month/Year Filed) (出願年月日)</p>	<p align="right">Priority Not Claimed 優先権主張なし</p>
<p>私は、第35編米国法典119条(e)項に基づいて下記の米 国特許出願規定に記載された権利をここに主張いたします。</p> <p>(Application No.) (出願番号)</p> <p>(Filing Date) (出願日)</p>	<p>I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.</p> <p>(Application No.) (出願番号)</p> <p>(Filing Date) (出願日)</p>
<p>私は、下記の米国法典第35編120条に基づいて下記の米 国特許出願に記載された権利、又は米国を指定している特許 協力条約365条(c)に基づき権利をここに主張します。また、 本出願の各請求範囲の内容が米国法典第35編112条 第1項又は特許協力条約で規定された方法で先行する米国特 許出願に開示されていない限り、その先行米国出願書提出日 以降で本出願書の日本国内または特許協力条約国際提出日ま での期間中に入手された、連邦規則法典第37編1条56項 で定義された特許資格の有無に関する重要な情報について開 示義務があることを認識しています。</p> <p>(Application No.) (出願番号)</p> <p>(Filing Date) (出願日)</p>	<p>I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.</p> <p>(Status: Patented, Pending, Abandoned) (現況: 特許許可済、係属中、放棄済)</p> <p>(Status: Patented, Pending, Abandoned) (現況: 特許許可済、係属中、放棄済)</p>

S00P1095US00

Japanese Language Declaration

日本語宣言書

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づく表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の声明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上犯のごとく宣誓を致します。

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may be jeopardize the validity of the application or any patent issued thereon.

S00P1095US00

Japanese Language Declaration

日本語宣言書

委任状： 私は下記の発明者として、本出願に関する一切の
手続きを米特許商標局に対して遂行する弁理士または代理人
として、下記の者を指名いたします。（弁理士、または代理
人の氏名及び登録番号を明記のこと）

POWER OF ATTORNEY: As a named inventor, I hereby
appoint the following attorney(s) and/or agent(s) to prosecute
this application and transact all business in the Patent and
Trademark office connected therewith (*list name and
registration number*)

Karl A. Limbach	18,689	Steven M. Everett	30,050	Cameron A. King	41,897
George C. Limbach	19,305	Alfred A. Equitz	30,922	Kyla L. Harriel	41,815
John K. Uilkema	20,282	Charles P. Sammut	28,901	Mayumi Maeda	40,075
Neil A. Smith	25,441	Mark C. Pickering	36,239	Michael R. Ward	38,651
Veronica C. Devitt	29,375	Patricia Coleman James	37,155	Roger S. Sampson	44,314
Ronald L. Yin	27,607	Kathleen A. Frost	37,328	Charles L. Hamilton	42,624
Gerald T. Sekimura	30,103	Alan A. Limbach	39,749	Andrew V. Smith	43,132
Michael A. Stallman	29,444	Douglas C. Limbach	35,249	Eric N. Hoover	37,355
Philip A. Girard	28,848	Seong-Kun Oh*		J. Thomas McCarthy	22,420
Michael J. Pollock	29,098			Joel G. Ackerman	24,307

* Recognition under 37 CFR 10.9(b)

書類送付先

Send Correspondence to:

Charles P. Sammut, Esq.
Limbach & Limbach L.L.P.
2001 Ferry Building
San Francisco, CA 94111-4262

直接電話連絡先：（名前及び電話番号）

Direct Telephone Calls to: (*name and telephone number*)

Charles P. Sammut
(415) 433-4150

唯一または第一発明者名

Full name of sole or first inventor:

YOSHINORI MATSUMOTO

発明者の署名

日付

Inventor's signature

Date

Yoshinori Matsumoto

2000/8/22

住所

Residence

KANAGAWA, JAPAN

国籍

Citizenship

JAPANESE

私書箱

Post Office Address

c/o SONY CORPORATION
7-35, Kitashinagawa 6-chome
Shinagawa-ku, Tokyo, 141-0001 JAPAN